



NOTES:

CLASS 560-C-3250 CONCRETE

2.10 C.F. / L.F.

1 CU. YD. = 12.86 L.F.

MINIMUM PERMISSIBLE GRADE 0.50%

PROVIDE 3/8" LIP AT EDGE OF ASPHALT WITH 1/8" TOLERANCE.

MINIMUM SUBGRADE COMPACTION 95% RELATIVE TO MAXIMUM (TOP 12-INCHES)

MAX. GRADE BREAK ON ROADWAYS SHALL NOT EXCEED 0.50%

ALL GUTTER SHALL BE "FLOW TESTED" PRIOR TO FINISH PAVING

SEE STANDARD 126 FOR JOINT DETAILS

DESIGN NOTES:

1. THIS CURB IS INTENDED FOR PRIVATE RESIDENTIAL USE ONLY.
2. USE ONLY IF IT IS DESIRED TO AVOID THE NEED FOR CUTTING DRIVEWAY APPROACHES THROUGH FULL-FACE CURB.

L:\Public Works - Engineering Standards\INDIO-124 5/19/2016 11:41 AM



Juan Raya 05/18/16
 JUAN RAYA, P.E. DATE
 CITY ENGINEER
 RCE 68510

REV.	DRAWN BY:	APP'D:	DATE:



WEDGE CURB

STANDARD PLAN No.: **124**

MAY 2016