



NOT TO SCALE

NOTES:

1. STANDARD RIBBON GUTTER SHALL BE USED ONLY IN PARKING LOTS.
2. ALL CONCRETE CONSTRUCTION SHALL BE CLASS 560-C-3250 CONCRETE.
3. RIBBON GUTTER THICKNESS TO BE 8" MINIMUM.
4. PLACE MINIMUM 6" CLASS 2 AGGREGATE BASE UNDER ENTIRE RIBBON GUTTER.
5. WEAKENED PLANE JOINTS SHALL BE REQUIRED AT EVERY 10' AND EXPANSION JOINTS AT EVERY 50' (SEE STANDARD 126 FOR JOINT DETAILS).
6. RIBBON GUTTER SECTION SHALL BE MODIFIED TO MEET AMERICANS WITH DISABILITIES ACT (ADA) STANDARDS, WHEN CROSSING ADA PATH OF TRAVEL.

L:\Public Works - Engineering Standards\INDIO-139 5/19/2016 11:13 AM



<i>Juan Raya</i>		05/18/16	
JUAN RAYA, P.E.		DATE	
CITY ENGINEER			
RCE 68510			
REV.	DRAWN BY:	APP'D:	DATE:



**STANDARD RIBBON
GUTTER
(TYPICAL SECTION)**

STANDARD PLAN No.:

139

MAY 2016